FORESTRY TILLERS

SSH - SSH/HP

Forestry tiller for PTO tractors with fixed teeth rotor.

160-500 hp

Ø 70 cm max

Depth 50 cm

All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.

STANDARD EQUIPMENT

Hydraulic rear hood	PTO shaft (SSH/HP)
Interchangeable inner antiwear plates in Hardox®	Friction clutches
Enclosed machine body	PTO shaft with cam clutch (SSH)
Inside lateral protection	Bolted-on rotor shafts (in forged steel)
Protection chains	Hydraulic top link
Transmission with side gearbox	Z style self ranging system of the PTO drive shaft/gearbox
Side gearbox with oil cooling system (SSH/HP)	Adjustable Hardox® counter-blade
Gearbox with freewheel	Special skids to go underground
Gearbox with oil cooling system (SSH/HP)	

OPTIONS

Anti clogging hood	Adjustable counter-blade (forest)
Bolted grid on rear hood	Skids extension
Anti clogging grid	Dozing blade
Stronger transmission for tractors up to (SSH 200 - 225 - 250)	Hydraulic support roller
Multiple tooth options	Increased hydraulic roller
W style self aligning device between PTO drive shaft/gearbox	

MODEL	SSH 150	SSH 175	SSH 200	SSH 225	SSH 250	SSH/HP 225	SSH/HP 250
Tractor (hp)	160-280	180-280	200-360 (400*)	200-360 (400*)	200-360 (400*)	360-500	360-500
PTO (rpm)	1000	1000	1000	1000	1000	1000	1000
Working width (mm)	1600	1840	2080	2320	2560	2320	2560
Total width (mm)	1980	2220	2472	2712	2952	2712	2952
Weight (Kg)	3690	3920	4850	5200	5640	5310	5680
Rotor diameter (mm)	910	910	910	910	910	910	910
Max shredding diameter (mm)	700	700	700	700	700	700	700
Max working depth (mm)	500	500	500	500	500	500	500
No. teeth type A/3+MH	58+4	66+4	78+4	88+4	98+4	88+4	98+4

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.

*Stronger trasmisson.

ROTOR TYPE A

NEW

A/3
(standard)

NEW

A/3/HD
(option)

F/3
(option)

MH
(side scraper)