

FORESTRY TILLERS

SSL SPEED

Forestry tiller for PTO tractors with fixed teeth rotor.



100-220 hp



Ø 30 cm max



Depth 30 cm

STANDARD EQUIPMENT

Hydraulic rear hood	Friction clutches (SSL/DT SPEED)
Enclosed machine body	PTO shaft with cam clutch
Inside lateral protection	Bolted-on rotor shafts (in forged steel)
Protection chains	Welded steel counter-blades
Transmission with side gearbox	Adjustable counter-blade (forest)
Gearbox with freewheel	

OPTIONS

Multiple tooth options	Hydraulic guard frame
Hydraulic top link	Hydraulic support roller

MODEL	SSL SPEED 150	SSL SPEED 175	SSL/DT SPEED 200	SSL/DT SPEED 225	SSL/DT SPEED 250
Tractor (hp)	100-160	110-160	120-220	130-220	140-220
PTO (rpm)	1000	1000	1000	1000	1000
Working width (mm)	1600	1840	2080	2320	2560
Total width (mm)	1920	2160	2400	2640	2880
Weight (Kg)	2000	2160	2600	2810	3030
Rotor diameter (mm)	595	595	595	595	595
Max shredding diameter (mm)	300	300	300	300	300
Max working depth (mm)	300	300	300	300	300
No. teeth type B/3+C/3/SS	44+4	50+4	58+4	66+4	74+4

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.

ROTOR TYPE B



B/3
(standard)



B/3/HD
(option)



G/3
(option)



C/3/SS
(side scraper)