STONE CRUSHERS

STC

Stone crusher for PTO tractors with fixed teeth rotor.

80-220 hp

Ø 30 cm max (stones)

Depth 20 cm

STANDARD EQUIPMENT

Hydraulic rear hood	Possibility to choose Transmission 540 / 1000 rpm (STC/ST)
Enclosed machine body (STC/DT)	PTO shaft with cam clutch
Centralized greasing hub (STC/DT)	Bolted-on rotor shafts (in forged steel)
Inside lateral protection	Flat pressed welded steel counter-blades
Dual row protection chains	Adjustable Hardox® counter-blade
Poly-V belts transmission	Adjustable skids
Gearbox with freewheel	Penetration skids

OPTIONS

Multiple tooth options	Dozing blade
Hydraulic top link	Grader blade (road kit) (STC/DT)

All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.

MODEL	STC/ST 125	STC/DT 150	STC/DT 175	STC/DT 200
Tractor (hp)	80-110	100-220	120-220	130-220
PTO (rpm)	540-1000	1000	1000	1000
Working width (mm)	1340	1580	1820	2060
Total width (mm)	1760	2010	2250	2490
Weight (Kg)	1850	2450	2690	2830
Rotor diameter (mm)	550	550	550	550
Max shredding diameter (mm)	300	300	300	300
Max working depth (mm)	200	200	200	200
No. teeth type STC/3+STC/3/HD	26+4	32+4	38+4	42+4

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.

STC/3
(standard)

STC/3/HD
(option)

STC/3/FP
(option)

STC/3/HD
(side scraper)